


30.900 MHz radio command

The ideal solution for apartment blocks


- Multi-user function.
- Available in versions from two to eight channels.
- 16,777,216 combinations.



Dimensions of transmitters



Dimensions of receivers (mm)



001RBE4N
001RBE42

Dimensions (mm/in)

MODEL	B	H	P	Weight (g/oz)
T152	45/1.77	92/3.62	15/0.59	34/1.19
T154	45/1.77	92/3.62	15/0.59	56/1.97
T158	45/1.77	92/3.62	15/0.59	56/1.97

Limits to use


MODEL	Range (m)
T15	50 ÷ 150 / 160 ÷ 500
T154	50 ÷ 150 / 160 ÷ 500
T158	50 ÷ 150 / 160 ÷ 500

Technical features

Type	T152 - T154 - T158
Batteries	1 x 12 V AAA
Combinations	16,777,216
Operating temperature (°C/°F)	-20 ÷ +55/-4 ÷ +131°C/°F
Material	ABS

The complete range



Code	Description
30.900 MHz transmitters	
001 T152	Bi-channel multi-user transmitter. 16,777,216 combinations.
001 T154	4-channel multi-user transmitter. 16,777,216 combinations.
001 T158	8-channel multi-user transmitter. 16,777,216 combinations.
30.900 MHz plug-in receivers	
001 AF150	Plug-in radio frequency card.
230 V AC surface-mounted radio module	
001 RBE42	230 V AC IP54 surface-mounted 4-channel radio module.
12 - 24 V AC - DC surface-mounted radio module	
001 RBE4N	12 - 24 V AC - DC IP54 surface-mounted 4-channel multi-user radio module.
	
Accessories for receivers	
001 TOP-A309N	Antenna.
001 TOP-RG58	Antenna cable.

