


868.35 MHz radio command

The ideal solution for residential premises




- Transmitter to transmitter self-learning.
- Even with transponder function.
- Multi-user function.
- 4,096 combinations.

Dimensions of transmitters (mm)




Dimensions of receivers (mm)



001RBE4N
001RBE42

Dimensions (mm/in)

MODEL	B	H	P	Weight (g/oz)
TOP-862NA	32/1.25	68/2.67	13/0.51	16/0.56
TOP-864NA	40/1.57	85/3.34	12/0.47	22/0.77



001RE862

Limits to use



MODEL	Range (m)
TOP-862NA	50 ÷ 150 / 160 ÷ 500
TOP-864NA	50 ÷ 150 / 160 ÷ 500

Technical features

Type	TOP-862NA - TOP-864NA
Batteries	2 X CR2016 LITHIUM
Combinations	4,096
Operating temperature (°C/°F)	-20 ÷ +55/-4 ÷ +131°C/°F
Material	ABS

The complete range



Code	Description
868.35 MHz transmitters	
001 TOP-862NA	Bi-channel multi-user transmitter. 4,096 combinations with self-learning function.
001 TOP-864NA	4-channel multi-user transmitter. 4,096 combinations with self-learning function.
868.35 MHz plug-in receivers	
001 AF868	Plug-in radio frequency card.
868.35 MHz surface-mounted receivers	
001 RE862	12 - 24 V AC - DC IP54 surface-mounted bi-channel receiver.
	
230 V AC surface-mounted radio module	
001 RBE42	230 V AC IP54 surface-mounted 4-channel radio module.
12 - 24 V AC - DC surface-mounted radio module	
001 RBE4N	12 - 24 V AC - DC IP54 surface-mounted 4-channel multi-user radio module.
	
Accessories for: 001TOP-862NA - 001TOP-864NA	
009 TAG	Glass transponder bulb.
001 P3V	Package of n. 2 3 V DC type CR2016 lithium batteries.
Accessories for receivers	
001 TOP-A862N	Antenna.
001 TOP-RG58	Antenna cable.



NOTE:
001TOP-862NA - 001TOP-864NA Max number of operators with differentiated code suggested for a single installation: 20.
Ex.: an apartment block with 20 customised garage doors.