


433.92 MHz radio command with KEY CODE

The ideal solution for both apartment blocks and multi-use settings



- Key Code transmitter, the password code protects the transmitter from unauthorised duplications.
- Available in either two or four channel versions.
- Even with transponder function.
- 4,294,967,896 combinations.
- Modern and elegant design.

Dimensions of transmitters




Dimensions (mm/in)

MODEL	B	H	P	Weight (g/oz)
TWIN2	32/1.25	68/2.67	13/0.51	16/0.56
TWIN4	32/1.25	68/2.67	13/0.51	16/0.56


Limits to use

MODEL	Range (m)
TWIN2	50 ÷ 150 / 160 ÷ 500
TWIN4	50 ÷ 150 / 160 ÷ 500

Dimensions of receivers (mm)



001RBE4N
001RBE42



001RE432
001RE432TW

Technical features

Type	TWIN2 - TWIN4
Batteries	2 X CR2016 LITHIUM
Combinations	4,294,967,896
Operating temperature (°C/°F)	-20 ÷ +55/-4 ÷ +131°C/°F
Material	ABS

The complete range



Code	Description
433.92 MHz transmitters with KEY CODE function	
001TWIN2	Bi-channel transmitter with KEY CODE function. 4,294,967,892 combinations.
001TWIN4	4-channel transmitter with KEY CODE function. 4,294,967,892 combinations.
433.92 MHz receivers with KEY CODE function	
001AF43TW	Plug-in radio frequency card.
433.92 MHz receivers with KEY CODE function	
001RE432TW	12 - 24 V AC - DC IP54 surface-mounted bi-channel receiver.
001AF43S	Plug-in radio frequency card.
001AF43SM	Plug-in radio frequency card with "eeprom" to store up to 128 codes (users).
433.92 MHz surface-mounted receivers	
001RE432	12 - 24 V AC - DC IP54 surface-mounted bi-channel receiver.
230 V AC surface-mounted radio module	
001RBE42	230 V AC IP54 surface-mounted 4-channel radio module.
12 - 24 V AC - DC surface-mounted radio module	
001RBE4N	12 - 24 V AC - DC IP54 surface-mounted 4-channel multi-user radio module.
Accessories for: 001TWIN2 - 001TWIN4	
009TAG	Glass transponder bulb.
001P3V	Package of n. 2 3 V DC type CR2016 lithium batteries.
Accessories for receivers	
001TOP-A433N	Antenna.
001TOP-RG58	Antenna cable.

